

## TRITON - SINUS Steel Armoured Expansion Joint

### PRODUCT DESCRIPTION



Sinusoidal-profiled permanent joint system with steel armouing. Installed within concrete slabs to ensure continuous load transfer between adjacent slabs. Protects slab edges from impact and wear. Allows for height adjustment to fit varying slab depths. Ideal for industrial floors, logistics, and distribution centre.

### KEY FEATURES

- Sinusoidal geometry for smooth traffic flow and effective load transfer.
- Complies with EN 2002/44/EC low-vibration standards.
- Reduces stress on forklift wheels → lower maintenance and operational costs.

### APPLICATIONS

- Industrial floor slabs
- Warehouses and logistics centres
- Multi-level mezzanines
- Exposed concrete slab edges
- Heavy-duty commercial areas



### TECHNICAL DATA

<b>Profile Height</b>	125-295mm	<b>Dowel</b>	5/6 pcs.
<b>Profile Length</b>	2,620mm (± 2mm)	<b>Dowel Size</b>	145 x 145 x 6mm 145 x 145 x 8mm 145 x 145 x 10mm
<b>Weight (Per Length)</b>	30.59 - 37.64kg	<b>Dowel Spacing</b>	500mm
<b>Steel Grade</b>	Joint : Q235 or Galvanised Dowels : Q355 Studs : Q195	<b>Dowel Sleeve</b>	Highly resistant ABS
<b>Top Strip</b>	H: 50mm D: 5mm (x2)	<b>Frangible Fastener</b>	Nylon bolt with steel nut
<b>Shear Studs</b>	28 pcs. (on both sides)		
<b>Footer</b>	H: variable D: 2mm		

## SPECIFICATIONS

The structural load capacity of the expansion joint, expressed in kilonewtons per linear meter (kN/m), depends on dowel density along the joint. Upon request, Triton can supply ultimate load values for specific failure modes. For information, this exercise is calculated with C25/30, S355 dowels 145 x 145 x 6mm with spacing of 600mm or 500mm and considering plate dowel depth at mid-depth.

Joint Opening	0	5	10	15	20	25
145mm x 145mm x 6 600cc	149	93	63	46	36	29
145mm x 145mm x 8 600cc	199	139	101	77	62	51
145mm x 145mm x 10 600cc	249	187	143	113	92	77

The first number is Joint strength in KN/m without considering the concrete breaking. The second number is smaller, as it is driven by concrete strength and also assuming plate dowel at mid-depth.

## INSTALLATION

- **Reference Line:** Stretch a string along the planned installation path to set a reference. Place the first joint profile parallel to this line.
- **Levelling:** Raise the profile to the final floor height using wedges or approved levelling systems.
- **Anchoring:** Drive or drill two vertical pins into the ground next to each anchor end. Add more pins along the length if needed for added stability.
- **Alignment Check:** Use a laser level to ensure accurate height and alignment. Inspect flatness across both width and length.
- **Fixing:** Weld the anchor pins to the profile. Where welding is not permitted, use adjustable feet.
- **Connection:** Insert the next profile into the connection point. Its height will align automatically; adjust the opposite end using wedges.
- **Repeat:** Continue the process until reaching a termination point (e.g., wall, column, or joint intersection).

## HEALTH AND SAFETY INFORMATION

All welding personnel must wear certified PPE, including:

- Eye and hearing protection
- Flame-resistant gloves
- Safety helmet and steel-toe boots
- Full-body protective clothing

These precautions meet safety standards and protect against thermal hazards, arc flash, airborne particles, and mechanical impact during installation.

### Disclaimer:

The information, drawings, and recommendations contained in this Technical Data Sheet are provided in good faith and are based on the best knowledge and experience of Triton Global Trading Limited at the time of publication. They are intended for general guidance only and must be evaluated and verified by the user for each specific application and site condition.

Triton Global Trading Limited makes no express or implied warranty regarding the accuracy, completeness, or suitability of the information for any particular purpose. The performance of the product may vary depending on installation methods, design parameters, environmental conditions, and maintenance practices, all of which are outside the control of Triton Global Trading Limited.

It is the sole responsibility of the designer, specifier, contractor or user to ensure that the product is suitable for its intended use, complies with relevant standards and regulations, and is installed in accordance with good construction practice and applicable project requirements.

Triton Global Trading Limited shall not be liable for any direct, indirect, or consequential loss or damage arising from the use of, or reliance upon, the information contained herein or from the improper installation or misuse of the product.

This Technical Data Sheet is subject to change without prior notice. The user should ensure that they are referring to the latest version available from Trident Global Trading Limited.

[www.tritonjoint.com](http://www.tritonjoint.com)